

KOMO[®]

product certificate

Number	K45997/02	Replaces	K45997/01
Issued	2011-03-15	Dated	2008-03-01
Valid until	Indefinite	Page	1 of 2



Steel for the reinforcement of concrete B500B: coils ArcelorMittal STFS

STATEMENT BY KIWA

This product certificate is issued on the basis of BRL 0501 "Steel for the reinforcement of concrete" (Betonstaal) dated 2010-09-01 by Kiwa, in accordance with the Kiwa Regulations for Product Certification.

Kiwa declares that legitimate confidence exists that the by the producer manufactured steel for the reinforcement of concrete comply with the technical specifications as laid down in this product certificate, provided that the steel for the reinforcement of concrete have been marked with the KOMO[®]-mark in the manner as indicated in this product certificate.

Bouke Meekma
Director Kiwa Nederland B.V.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.
Sir W. Churchill laan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 70 414 44 00
Fax +31 70 414 44 20
www.kiwa.nl

Holder of Certificate
ArcelorMittal STFS
Boulevard Aloyse Meyer
4241 ESCH-SÜR-ALZETTE
Luxemburg
Tel. +352 57 12 81
Fax +352 54 88 26



Steel for the reinforcement of concrete B500B: coils

PRODUCT SPECIFICATION

General

Steel for the reinforcement of concrete B500B (coils) are in accordance with the requirements of chapter 4 of guideline 0501 and with that of NEN 6008.

The products are meant to be used in constructions of concrete.

Classification : B 500B
 Production method: Hot rolled cold stretched
 Nominal size : 8, 10, 12, 14 and 16 mm
 Delivery condition : coils (compact spooled)

The quality mark B500B fulfils the requirements of the old quality mark FeB 500HK

Marking

The products are marked with a label with upon it at least on a clear and indelible way:

- the KOMO[®]-logo and the certificate number, figure 1;
- the classification B500B,
- the diameter;
- the rolling mark;
- heatnumber/castnumber/coilnumber;
- name of the certificate holder;
- BRL 0501.

Place of the label: at least one label per coil.


Steel for the reinforcement of concrete is marked on the following way:

On two rib rows by thickened ribs, with the code (2-7), figure 2.

Place of the mark: on a mutual distance of ± 1 meter. The position of the transverse ribs may also be in reverse.



Figure 1



(2-7) Figure 2

RECOMMENDATIONS FOR USERS

Check at the time of delivery whether:

- the producer has delivered in conformity with the agreement;
- the mark and marking method are correct;
- the products do not show any visible defects due to transport.

If you should reject a product on the basis of the above, please contact:

- ArcelorMittal STFS
- and if necessary:
- Kiwa Nederland B.V.

Consult for the proper method of storage and transport NEN 6722 and/or NEN-EN 13670.

LIST OF DOCUMENTS

NEN 6008	Betonstaal
NEN 6722	Voorschriften Beton – Uitvoering
NEN-EN 13670	Het vervaardigen van betonconstructies

* For the actual version of the standards see the latest version of the BRL 0501 or latest amendment sheet